

# Amazingly eye-catching appliances

Energy lives here™

Challenge reality and rethink what's possible in appliance appeal.



- **Replacing standard ICP**
  - 20% higher gloss
  - 10% improved stiffness
- **Replacing ABS**
  - 20% cost savings<sup>1</sup>
  - 14% lower density for lighter weight parts

With superior gloss and stiffness compared to standard impact copolymers (ICP), Achieve™ advanced polypropylene (PP) allows brand owners to economically produce amazingly eye-catching appliances. Achieve is perfect for upgrading existing PP solutions or replacing over-engineered acrylonitrile butadiene styrene (ABS).

## Create new appliance designs

Through collaboration, Achieve enables customers to create glossier and lighter appliance designs - that can do more with less. Achieve is widely recyclable and can expand end-of-life options.

Achieve can be used in appliance parts such as:

- **Major appliances** - appearance parts in washing machines and refrigerators
- **Small appliances** - appearance parts in vacuums, electric fans and garment steamers


With more finely dispersed rubber, Achieve enables manufacturers to produce appliance parts with gloss levels 20 percent higher than standard ICP and comparable to ABS. Capitalizing on its gloss and stiffness, designers can deliver parts with high-end product appearance and performance.

## Cost-saving solutions

Achieve 7123KNE1 is a perfect replacement for over-engineered ABS parts, delivering savings through reduced weight, lower raw material costs, and improved processing energy consumption.


1. Economic cost calculation is based on the ICIS average ABS price in North East Asia in February 2018. Using a 0.8kg ABS part as an example, savings include the unit price difference between ABS and Achieve 7123KNE1, as well as density benefits. Actual total savings are based on the weight of a customer's replacement part and other associated costs.

**Figure 1:**  
Selected property data for Achieve 7123KNE1 and the reference impact copolymer. Highlights improved aesthetics.



Note: all data from PDS, reference ICP gloss data from WOMS: MAC201408.0009-04.

**Figure 2:**  
Selected property data for Achieve 7123KNE1 and the reference ABS. Highlights cost saving opportunities.



Note: Achieve 7123KNE1 data from PDS, ABS gloss/HDT/Flexural modulus from WOMS: MAC201408.0009-04, density, rockwell hardness from PDS



Grade	MFR (230°C/2.16 kg) g/10 min	Tensile stress at yield MPa	Flexural modulus 1% secant (2.0 mm/min) – MPa	Flexural modulus 1% secant (0.051 in/min) – psi	Notched Izod impact (23°C) – J/m	Notched Izod impact (23°C) – kJ/m <sup>2</sup>	Heat distortion temperature (0.45 MPa) – °C	Gardner gloss (60°)
Achieve 7123KNE1	11	30.8	1680	228000	85	6.9	102	89
	ASTM D1238	ISO 527-2	ISO 178	ASTM D790A	ASTM D256A	ISO 180/1A	ISO 75-2/Bf	ASTM D523

Values given are typical and should not be interpreted as specifications. Data generated by or on behalf of ExxonMobil Chemical. Test methods are based on the ASTM and/or ISO standards.

## Use Achieve™ advanced PP to challenge reality in appliance appeal.

©2018 ExxonMobil. ExxonMobil, the ExxonMobil logo, the interlocking "X" device and other product or service names used herein are trademarks of ExxonMobil, unless indicated otherwise. This document may not be distributed, displayed, copied or altered without ExxonMobil's prior written authorization. To the extent ExxonMobil authorizes distributing, displaying and/or copying of this document, the user may do so only if the document is unaltered and complete, including all of its headers, footers, disclaimers and other information. You may not copy this document to or reproduce it in whole or in part on a website. ExxonMobil does not guarantee the typical (or other) values. Any data included herein is based upon analysis of representative samples and not the actual product shipped. The information in this document relates only to the named product or materials when not in combination with any other product or materials. We based the information on data believed to be reliable on the date compiled, but we do not represent, warrant, or otherwise guarantee, expressly or impliedly, the merchantability, fitness for a particular purpose, freedom from patent infringement, suitability, accuracy, reliability, or completeness of this information or the products, materials or processes described. The user is solely responsible for all determinations regarding any use of material or product and any process in its territories of interest. We expressly disclaim liability for any loss, damage or injury directly or indirectly suffered or incurred as a result of or related to anyone using or relying on any of the information in this document. This document is not an endorsement of any non-ExxonMobil product or process, and we expressly disclaim any contrary implication. The terms "we," "our," "ExxonMobil Chemical" and "ExxonMobil" are each used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliate either directly or indirectly stewarded.

Contact us for more information:  
[exxonmobilchemical.com](http://exxonmobilchemical.com)

P0418-038E49

**ExxonMobil**  
Energy lives here™