

Oil-free solution for comfortable TPE applications

Energy lives here™



Vistamaxx™ polymers formulation can eliminate the sticky touch caused by oil blooming

- Oil-free solution provides better anti-slip performance especially under wet condition
- Excellent compatibility with polyolefin-based substrates
- Cost effective with good balance of property and touch feel

Typical formulation with Vistamaxx polymers:

- 50 to 90% Vistamaxx 6202/6502
- 5 to 20% Vistamaxx 8880
- 0 to 30% PP
- 0 to 30% CaCO₃

Features	Benefits
Oil-free	<ul style="list-style-type: none"> • Anti-slip especially under wet condition • No sticky feel due to oil blooming
Durability	<ul style="list-style-type: none"> • Excellent compatibility with polyolefin based substrates • Improved toughness with tear and tensile strength
Comfortable touch	<ul style="list-style-type: none"> • Improved grip and reduced fatigue • Good ergonomics and appearance
Clarity	<ul style="list-style-type: none"> • Design flexibility with good colorability, semi-transparency
Improved economics	<ul style="list-style-type: none"> • Cost effectiveness • Lower density • Reprocessable • High filler loading acceptance

Vistamaxx grade	MFR 230°C/ 2.16 kg ExxonMobil method g/10 min	Density ¹ 23°C ASTM D1505, g/cm ³	Hardness 15 sec ASTM D2240, shore D/A	Tensile stress ¹ at break ASTM D638, MPa (psi)	Elongation ¹ at break ASTM D638, %	Flex mod ^{1,2} 1% secant ASTM D790 MPa (psi)	Tear strength ¹ Die C ASTM D624, kN/m (lbf/in)	Vicat softening point 200 g ExxonMobil method, °C (°F)
6202	20	0.862	64A	>5.52 (>800)	>800	12.8 (1860)	32.0 (183)	45.2 (113)
6502	45	0.865	71A	>7.58 (>1100)	>800	20.4 (2960)	40.6 (232)	51.4 (125)

	Viscosity at 190°C (374°F) ExxonMobil method cP (mPa·s)	Density ExxonMobil method g/cm ³	Durometer hardness (Shore C) ASTM D2240	Tensile strength at break ExxonMobil method, MPa (psi)	Elongation at break ExxonMobil method, %	Melting point, Tm ExxonMobil method, °C (°F)
8880	1200	0.879	53	6.2 (900)	1237	97 (206)

1. All physical properties were measured on specimens cut from compression molded plaques per ASTM D4703, Procedure A, Type I and conditioned at 23°C for a minimum of 40 hours per ASTM D618 prior to testing.
2. 1% secant at break.

Creating differentiated solutions. Together.

Visit the ExxonMobil Chemical booth (6.2G61) to find out how Vistamaxx™ can create value to achieve new levels of performance with lower formulation and processing costs.



©2018 ExxonMobil. ExxonMobil, the ExxonMobil logo, the interlocking "X" device and other product or service names used herein are trademarks of ExxonMobil, unless indicated otherwise. This document may not be distributed, displayed, copied or altered without ExxonMobil's prior written authorization. To the extent ExxonMobil authorizes distributing, displaying and/or copying of this document, the user may do so only if the document is unaltered and complete, including all of its headers, footers, disclaimers and other information. You may not copy this document to or reproduce it in whole or in part on a website. ExxonMobil does not guarantee the typical (or other) values. Any data included herein is based upon analysis of representative samples and not the actual product shipped. The information in this document relates only to the named product or materials when not in combination with any other product or materials. We based the information on data believed to be reliable on the date compiled, but we do not represent, warrant, or otherwise guarantee, expressly or impliedly, the merchantability, fitness for a particular purpose, freedom from patent infringement, suitability, accuracy, reliability, or completeness of this information or the products, materials or processes described. The user is solely responsible for all determinations regarding any use of material or product and any process in its territories of interest. We expressly disclaim liability for any loss, damage or injury directly or indirectly suffered or incurred as a result of or related to anyone using or relying on any of the information in this document. This document is not an endorsement of any non-ExxonMobil product or process, and we expressly disclaim any contrary implication. The terms "we," "our," "ExxonMobil Chemical" and "ExxonMobil" are each used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliate either directly or indirectly stewarded.